



Vanguard Collection

V 45 SC DT RCG (ER) Reference

Case Vanguard case

Stainless Steel Hand polished

Water resistant up to 30 meters

Width: 44 mm x Length: 53.7 mm x Thickness: 12.7 mm

Red ergal inserts on both sides of the case

Sapphire crystal

Brushed finish Dial

Applique numerals meticulously painted and applied by hand

Hours, Minutes, Seconds, Date **Functions**

Winding shaft with 3 positions: 1. Winding. 2. Date setting 3. Time setting Instructions

Movement MVT FM 2536-SCDT

Self-winding movement with bidirectional rotor system

Power reserve of 42 hours

191 components

25 iewels

Diameter: Ø 26.20 mm. Thickness: 5.35 mm

Balance wheel frequency set at 28,800 alternations per hour

Côtes de Genève and brushing soleil papier on the bridges and the rotor Movement

Decoration

Circular graining on the two sides of the main plate
Chamfering of the bridges 24k gold bath and rhodium plating of the components 24k

gold finish on the written engravings Circular brushing of the rotor ball bearing

Brushing soleil papier on the barrel Polishing at 45° and brushing soleil of the ratchet Polished and blued screws

Bracelet Hand sewn alligator strap

Buckle Stainless steel folding buckle

Hand polished